

CODE	MODEL	TYPE	POWER SUPPLY	SERIES
10291002	M9TTE80	SOLID TOP	ELECTRIC	MILO 900

DESCRIPTION

ELECTRIC SOLID TOP**TECHNICAL DATA**

Electric power (kW)	12
Standard voltage* (kW)	380-415 V 3 N ~
N° of cooking zones	4X3,0KW
IPX Protection Grade (mm)	IPX4

DIMENSIONS DATA

Product dimensions (mm)	800W x 900 P x 290 H
Net weight (kg)	100
Gross weight (kg)	117
Packaging dimensions (m3)	845 x 972 x 624
Packaging volume (m3)	0.51

CONSTRUCTIONAL FEATURES

Worktop made of 2mm-thick AISI 304 stainless steel with Scotch Brite finish. Control panel, side panels and back panel in 1mm thick AISI 304 stainless steel with Scotch Brite finish. Precise juxtaposition of worktops ensuring maximum hygiene. Stainless steel brackets are provided as standard, allowing the appliances to be effectively fixed side by side (optional gasket). Sloping back guard, with built-in exhausted grate and removable steel closing grid. Adjustable feet with scratch-resistant sole made of insulating plastic material.

TECHNICAL FEATURES

Solid top with radiant plate in 15 mm thick alloy steel with satin chromed finish. Plate embedded in the worktop, surrounded by water-tight perimeter with large drain hole and GNI/3 molded collection tray, easily removable for emptying and cleaning operations. Differentiated zones with independent temperature control from 50° to 350°C, heated by tungsten, radiant resistive, high-efficiency heating elements, which ensure fast response time. Energy regulator with 9 levels. Ergonomic, athermic control knob with built-in operating LED.

CODE

10291002

MODEL

M9TTE80

TYPE

SOLID TOP

POWER SUPPLY

ELECTRIC

SERIES

MILO 900

DESCRIPTION

ELECTRIC SOLID TOP**TECHNICAL DRAWING****CONNECTIONS**

E = ELECTRIC

380-415 V 3 N ~