

| CODE            | MODEL             | TYPE               | POWER SUPPLY    | SERIES          |
|-----------------|-------------------|--------------------|-----------------|-----------------|
| <b>11391002</b> | <b>MDPE45CL2A</b> | <b>PASTACORNER</b> | <b>ELECTRIC</b> | <b>MILO 900</b> |

## DESCRIPTION

**PASTACORNER: ELECTRIC PASTA COOKER WITH 2 BASKET LIFTING MODULES (3+3 LIFTERS)**

## TECHNICAL DATA

|                           |         |
|---------------------------|---------|
| Electric power (kW)       | 9.2     |
| N° of cooking zones       | 1x9,0kW |
| N° of tanks               | 1x45lt  |
| IPX Protection Grade (mm) | IPX4    |

## DIMENSIONS DATA

|                           |                      |
|---------------------------|----------------------|
| Product dimensions (mm)   | 800W x 900 P x 900 H |
| Net weight (kg)           | 120                  |
| Gross weight (kg)         | 142                  |
| Packaging dimensions (m3) | 845 x 972 x 1264     |
| Packaging volume (m3)     | 1.2                  |



## CONSTRUCTIONAL FEATURES

Worktop made of 2mm-thick AISI 304 stainless steel with Scotch Brite finish. Control panel, side panels and back panel in 1mm thick AISI 304 stainless steel with Scotch Brite finish. Precise juxtaposition of worktops ensuring maximum hygiene. Stainless steel brackets are provided as standard, allowing the appliances to be effectively fixed side by side (optional gasket). Sloping back guard with built-in exhaust grate and removable steel closing grid. Adjustable feet made of AISI 304 stainless steel with scratch-resistant sole made of insulating plastic material. Foot extension 60mm, standard worktop height 900mm (minimum 895, maximum 955).

## TECHNICAL FEATURES

Electric pasta cooker with seamless, AISI 316 stainless steel tank with widely radiused edges for easier and more effective cleaning and front area with chute and perforated top for basket support. Heating achieved by special tungsten heating elements placed outside the tank. Power adjustment with 3-position selector switch and ergonomic, athermic control knob with built-in operating LED. Two-way solenoid valve for loading and maintaining water level in the tank, stainless steel front spout and automatic level control: in case of water shortage heating is inhibited. Ø1" drain tap with ergonomic handle, lower compartment fully enclosed by AISI 304 stainless steel panelling for maximum hygiene. Two lifting modules with independent motorized lifters, controlled by electronic card: depending on the cooking time set for the specific lifter, when the cooking is complete it emits an acoustic signal and automatically extracts the basket from the tank, which remains raised in the stand-by position. Baskets not included.

Lower compartment closed by AISI 304 stainless steel hinged door, opening to the left, honeycombed and with assisted closing hinges and space-saving ergonomic handle.

## ACCESSORIES(not included)

| Code   | Model    | Description                    |
|--------|----------|--------------------------------|
| 861138 | GNI/3A   | BASKET PASTAC. GNI/3A          |
| 861143 | GNI/6DXA | RIGHT BASKET PASTAC.GNI/6 H215 |
| 861144 | GNI/6SXA | LEFT BASKET PASTAC.GNI/6 H215  |

| CODE            | MODEL             | TYPE               | POWER SUPPLY    | SERIES          |
|-----------------|-------------------|--------------------|-----------------|-----------------|
| <b>11391002</b> | <b>MDPE45CL2A</b> | <b>PASTACORNER</b> | <b>ELECTRIC</b> | <b>MILO 900</b> |

DESCRIPTION

**PASTACORNER: ELECTRIC PASTA COOKER WITH 2 BASKET LIFTING MODULES (3+3 LIFTERS)**

TECHNICAL DRAWING

